

CLAY CUTTER™ DRY

DRY DRILLING FLUID POLYMER



DESCRIPTION

CLAY CUTTER DRY is an easy-mixing, water-soluble, polymer used in horizontal and vertical drilling applications. CLAY CUTTER DRY is certified to NSF/ANSI Standard 60, Drinking Water Treatment Chemicals - Health Effects.

RECOMMENDED USE

CLAY CUTTER DRY should be added to fresh or saltwater drilling fluids to increase cuttings returns and reduce torque and drag when drilling in reactive clay soils. This additive may be used in both HDD and Waterwell applications.

CHARACTERISTICS

- Eliminates clay and shale swelling, bit balling, and sticking problems
- Increases returns back to the surface
- Non-hazardous
- Quick mixing and rapid yield in freshwater
- Reduces torque and pullback pressures
- Stabilizes the borehole



MIXING AND APPLICATION

SUPER GEL-X/HYDRAUL-EZ systems: add 0.25 to 1 lb per 100 gallons (113 g to 0.45 kg per 450 liters) to stabilize reactive clay formations.

When using a non-clay freshwater system add 0.5 to 2 lbs per 100 gallons (227 g to 0.9 kg per 450 liters) to stabilize clay formations, increase returns to surface, and reduce torque, drag, and bit balling.

PACKAGING

20 lb (9 kg) pails, 60 per pallet. All pallets are plastic-wrapped.

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: JULY 2015

© 2015 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

FORM: TDS_CLAY_CUTTER_DRY_AM_EN_201507



CETCO