

# CETCO<sup>®</sup> DEFOAMER

## FOAM BREAKER

### DESCRIPTION

CETCO DEFOAMER is a non-ionic silicone solution designed to reduce surface tension and break foam bubbles over a wide variety of conditions.

### RECOMMENDED USE

Defoam in various media encountered in waterwell, large diameter shaft holes, geothermal, and oilfield drilling.

### CHARACTERISTICS

- Compatible with fresh and saltwater systems
- Immediate defoaming action with long term defoaming prevention
- Non-flammable; safe for potable waterwells
- Reduces corrossions caused by entrained air in drilling fluids



### MIXING AND APPLICATION

Surface/Pit Defoaming	Emit fine spray directly on foam
Slug Treatment	1-2 pints per 1,000 gallons (0.5-1 liters per 4 m <sup>3</sup> ) drilling fluid

### PACKAGING

42 lb (18.9 kg) pails, 28 per pallet. All pallets are plastic-wrapped.

North America: 847.851.1800 | 800.527.9948

© 2013 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.CETCO.com](http://www.CETCO.com). CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.

UPDATED: SEPTEMBER 2013

TDS\_CETCODEFOAMER\_AM\_EN\_201309\_v1

**CETCO**<sup>®</sup>

An **AMCOL** Company

[www.CETCO.com](http://www.CETCO.com)