

SUPER PAC™ XTRA-LOW

LIQUID POLYANIONIC CELLULOSIC POLYMER

DESCRIPTION

SUPER PAC XTRA-LOW is a low viscosity, liquid multi-purpose polymer. SUPER PAC XTRA-LOW enhances the beneficial properties of bentonite and polymer drilling fluids.

ADVANTAGES

This low viscosity polymer aids in the control of reactive and unconsolidated formations by reducing filtrate and whole fluid loss. SUPER PAC XTRA-LOW assists hole cleaning in HDD work and increases penetration rates in vertical wells by not significantly raising viscosities.

CHARACTERISTICS

- Helps prevent hydration of shales and clays
- Highly dispersible and mixes at low shear
- Minimized viscosity increase for increased flow
- Reduces filtrate and fluid loss to reactive and permeable or unconsolidated formations
- Suitable for use in fresh and saltwater drilling fluids

MIXING AND APPLICATION

Mix directly into a well circulated mud pit or through venturi hopper. Add 0.5 to 1 quart per 100 gallons (0.5 to 1 liter per 380 liters) of existing bentonite drilling fluid for hole stabilization.

PACKAGING

42 lb (18.9 kg) pail, 32 per pallet. All pallets are plastic-wrapped.



North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: JULY 2015

© 2015 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

FORM: TDS_SUPER_PAC_XTRA-LOW_AM_EN_201507



CETCO®