

# PUREGOLD<sup>®</sup> LUBE

## PREMIUM GRADE LUBRICANT

### DESCRIPTION

PUREGOLD LUBE is an environmentally safe premium grade lubricant, free of petroleum hydrocarbons and metals. PUREGOLD LUBE is a tool joint lubricant designed for use in environmental drilling.

### RECOMMENDED USE

PUREGOLD LUBE is used to lubricate threads on drill rod stems, auger bolts, and sampling devices. Helps prevent seizing and reduces thread wear. PUREGOLD LUBE may also be used to lubricate other tools and instruments used in environmentally sensitive applications.

### CHARACTERISTICS

- Chemically stable
- Easily removed during decontamination
- Maintains sample integrity
- Provides maximum protection to the drill string
- Reduces friction and helps prevent seizing
- Reduces thread wear
- Remains workable in cold temperatures
- Washout resistant

### MIXING AND APPLICATION

PUREGOLD LUBE should be applied liberally onto threads using a stiff brush. After joint is tightened, excess or extruded material should be removed.

### PACKAGING

8 lb (3.6 kg) plastic pails, 100 per pallet. All pallets are plastic-wrapped.

North America: 847.851.1800 | 800.527.9948 | [www.CETCO.com](http://www.CETCO.com)

UPDATED: JULY 2015

© 2015 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.CETCO.com](http://www.CETCO.com). CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

FORM: TDS\_PUREGOLD\_LUBE\_AM\_EN\_201507



**CETCO**<sup>®</sup>