

General Purpose 200 Mesh Powder

Revised 05/25/01

VOLCLAY® ACCU-GEL

General A high-efficiency sodium bentonite exhibiting superior thixotropic

Description properties and characterized by high viscosity and complete dispersion.

Functional General purpose suspending, emulsifying, and plasticizing agent used in

Use industrial products such as asphalt emulsions and rock wool insulation.

Purity Hydrous aluminum silicate comprised principally of the clay mineral

montmorillonite. Contains minor amounts of feldspar, calcite, and quartz.

Chemical Dioctahedral smectite, an expanding layer silicate:

Formula $(Na,Ca)_{0.33} (Al_{1.67}Mg_{0.33})Si_4O_{10}(OH)_2 \cdot nH_2O$

Elemental Composition

Typical analysis – moisture free.

SiO₂ 63.02 % 21.08 % Al_2O_3 Fe₂O₃ 3.25 % FeO 0.35 % 2.67 % MgO Na₂O 2.57 % CaO 0.65 % Trace 0.72 % LOI 5.64 %

Moisture Maximum 12% as shipped.

Dry Particle

Size

Minimum 65% finer than 200 mesh (74 microns).

Wet Particle

Size

Minimum 94% finer than 200 mesh (74 microns). Minimum 92% finer than 325 mesh (44 microns).

pH 8.0 - 10.0 @ 5% solids.

Viscosity 15 cps minimum @ 6.25% solids.

Packaging 50 or 100 pound multi-wall paper bags, or bulk.

Disclaimer: The information and data contained herein are believed to be accurate and reliable. ACC makes no warranty of any kind and accepts no responsibility for the results obtained through application of this information