## **SWELLTITE® WATERPROOFING MEMBRANE**



## **SWELLTITE®** WATERPROOFING MEMBRANE

# COMPOSITE BENTONITE WATERPROOFING SYSTEM

SWELLTITE® waterproofing membrane is a highly effective membrane consisting of a sodium bentonite compound integrally bonded to a geomembrane liner. This composite combines the active waterproofing benefits of sodium bentonite with the strength and durability of a thick geomembrane liner.

Unlike other membrane systems that require precise installation, SWELLTITE's reactive bentonite compound can expand to seal small punctures in the membrane. SWELLTITE works by forming a continuous membrane upon hydration with water. When confined under pressure, the swell is controlled, forming a dense, positive seal against the concrete. Proven quality and ease of installation have made SWELLTITE a market leader in the waterproofing industry. More than 50 million square feet of SWELLTITE have been installed worldwide on projects such as split-slab plaza decks, backfilled foundation walls, and cut-and-cover tunnels.

#### **APPLICATIONS**

Split-Slab Decks
Cut-and-Cover Tunnels
Backfilled Walls
CMU Foundation Walls

Earth-Covered Structures



## **SWELLTITE® WATERPROOFING MEMBRANE**







## **Exceptional Waterproofing Performance:**

#### **Protection from Water Ingress:**

- More than 50 million square feet installed and 20 years of proven waterproofing success.
- Combines the active waterproofing benefits of sodium bentonite with the strength and puncture resistance of a thick geomembrane liner.
- A 100% solids thermoplastic product that is flexible as well as self-sealing.

#### **Installation Benefits and Features:**

#### **Fast and Easy:**

- · Ready for use and requires no set-up.
- Overlapped seams and mechanical fasters eliminates installation variables in the field.
- The geomembrane layer eliminates the need for protection board for most applications.

#### **Versatility:**

- Proven effective for split-slab, plaza deck, protected membrane roof and landscaped assemblies.
- Suitable for use in new construction as well as retrofit applications.
- Can be installed in temperatures as low as 0°F.



#### SWELLTITE® qualifies for the HydroShield™ Quality Assurance Program.

Protect your structure from water ingress with the industry's leading quality assurance program. This proven, systematic approach provides a no-dollar-limit warranty for 100 percent, non-prorated protection for the entire term of the warranty. For more information visit cetco.com.

cetco@mineralstech.com | cetco.com | 800.527.9948

