



August 15, 2018

N-FLASH

LEED™ PRODUCT INFORMATION

N-FLASH is a 60-mil thick, uncured neoprene rubber flashing used as an accessory component with Strataseal HR hot-applied rubberized asphalt waterproofing and roofing system.

MANUFACTURING LOCATION

CETCO certifies that N-Flash is manufactured in Cartersville, GA. If your project falls within a 500-mile radius of this location, the product is considered to be locally produced material and can help contribute to earning Materials & Resources – Credit 5.1 and Credit 5.2.

RECYCLED CONTENT

CETCO certifies that N-Flash is manufactured with a nominal 0% post-consumer recycled material with regards to contributing toward earning Materials & Resources – Credit 4.1 and Credit 4.2.

VOC CONTENT

CETCO certifies that N-Flash contains 0 g/L Volatile Organic Compounds (VOCs). EQ Credit 4.1 and EQ Credit 4.2 pertain to materials that are to be used in the interior of the building. CETCO waterproofing products are applied onto the exterior of the structure and therefore are not subject to the intent of EQ Credit 4.1 and EQ Credit 4.2. However, CETCO has provided the volatile organic content (VOC) of N-Flash herein.

CONSTRUCTION WASTE MANAGEMENT

In areas where facilities exist, the following N-Flash materials are recyclable and can contribute to earning MR Credit 2.1 and MR Credit 2.2:

Wood Pallet	wood	55-lbs
-------------	------	--------

LEED is a trademark of the U.S. Green Building Council

