

CETCO® DEFOAMER

FOAM BREAKER

DESCRIPTION

CETCO DEFOAMER is a non-ionic silicone solution designed to reduce surface tension and break foam bubbles over a wide variety of conditions.

RECOMMENDED USE

Defoam in various media encountered in waterwell, large diameter shaft holes, geothermal, and oilfield drilling.

CHARACTERISTICS

- Compatible with fresh and saltwater systems
- Immediate defoaming action with long term defoaming prevention
- Non-flammable; safe for potable waterwells
- Reduces corrosions caused by entrained air in drilling fluids

MIXING AND APPLICATION

| | |
|-----------------------|--|
| Surface/Pit Defoaming | Emit fine spray directly on foam |
| Slug Treatment | 1-2 pints per 1,000 gallons (0.5-1 liters per 4 m ³) drilling fluid |

CETCO DEFOAMER can be conveniently mixed in a lawn and garden sprayer for easy application.

PACKAGING

~38 lb (18.9 kg) pails, 32 per pallet. All pallets are plastic-wrapped.



North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: APRIL 2023

© 2023 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

