

SUPER PAC™

DRILLING FLUID ENHANCER

DESCRIPTION

SUPER PAC is an easy mixing, liquid polymer that enhances the properties of a bentonite drilling fluid. When added to HYDRAUL-EZ or SUPER GEL-X, SUPER PAC creates an ideal fluid for drilling in a variety of conditions.

RECOMMENDED USE

This multifunctional polymer is designed for use as a drilling fluid additive for inhibition of clay and shale, minimizing fluid loss to the formation, and increasing viscosity for cuttings transport and suspension.

CHARACTERISTICS


- Increases viscosity of drilling fluid
- Inhibits the hydration of clays and shale
- Provides filtration control in both fresh and saltwater
- Reduces fluid loss in permeable formations

MIXING AND APPLICATIONS

Mix at low shear through a mud hopper. Add 0.5 to 1 quart per 100 gallons (0.5 to 1.0 liter per 380 liters) of existing bentonite drilling fluid for hole stabilization.

PACKAGING

42 lb (19.1 kg) pail, 32 per pallet. All pallets are plastic-wrapped.



North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: MAY 2019

© 2019 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit www.CETCO.com. CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

FORM: TDS_SUPER_PAC_AM_EN_201606



CETCO®